



OPCIONES DE CNC CYBELEC y DELEM

PLEGADORAS HIDRÁULICAS SERIE **POWER-BEND PRO / FALCÓN** (3 o 4 EJES)

| Características Técnicas | Longitud de plegado (mm.) | Potencia (TM.) | Distancia entre montantes (mm.) | Velocidad rápida (mm/s) | Potencia motor (kw.) | Escote (mm.) |
|--------------------------|---------------------------|----------------|---------------------------------|-------------------------|----------------------|--------------|
| PB-PRO 1270-40           | 1270                      | 40             | 1050                            | 140                     | 5,5                  | 350          |
| PB-PRO 2100-40           | 2100                      | 40             | 1700                            | 140                     | 5,5                  | 350          |
| PB-PRO 2100-60           | 2100                      | 60             | 1700                            | 200                     | 7,5                  | 410          |
| PB-PRO 3100-100          | 3100                      | 100            | 2600                            | 200                     | 7,5                  | 410          |
| PB-PRO 3100-135          | 3100                      | 135            | 2600                            | 200                     | 11                   | 410          |
| PB-PRO 3100-175          | 3100                      | 175            | 2600                            | 180                     | 15                   | 410          |
| PB-PRO 3100-220          | 3100                      | 220            | 2600                            | 180                     | 18,5                 | 410          |
| PB-PRO 3100-260          | 3100                      | 260            | 2600                            | 140                     | 22                   | 410          |
| PB-PRO 3100-320          | 3100                      | 320            | 2600                            | 140                     | 30                   | 410          |
| PB-PRO 3100-400          | 3100                      | 400            | 2550                            | 110                     | 30                   | 510          |
| PB-PRO 4100-135          | 4100                      | 135            | 3600                            | 200                     | 11                   | 410          |
| PB-PRO 4100-175          | 4100                      | 175            | 3600                            | 180                     | 15                   | 410          |
| PB-PRO 4100-220          | 4100                      | 220            | 3600                            | 180                     | 18,5                 | 410          |
| PB-PRO 4100-260          | 4100                      | 260            | 3600                            | 140                     | 22                   | 410          |
| PB-PRO 4100-320          | 4100                      | 320            | 3600                            | 140                     | 30                   | 410          |
| PB-PRO 4100-400          | 4100                      | 400            | 3550                            | 110                     | 30                   | 510          |
| PB-PRO 6100-220          | 6100                      | 220            | 5100                            | 130                     | 18,5                 | 410          |
| PB-PRO 6100-320          | 6100                      | 320            | 5100                            | 80                      | 30                   | 410          |
| PB-PRO 6100-400          | 6100                      | 400            | 5100                            | 80                      | 30                   | 510          |